268 HANDHELD CASES

292

318

342

370


1500 Series **Universal Smart Enclosure**

Product overview

The UK manufactured 1500 Series Universal Smart Enclosure has a premium quality and modern aesthetic with many features and benefits and is available in black, white or grey with the choice of a solid or vented body. The innovative and versatile 45° angled enclosure and bracket allows it to be mounted directly onto irregular corners and walls. It has multi-level PCB mounting bosses with one level designed to fit development boards such as the Raspberry Pi.



Key features



Multiple PCB mounting points

Designed to accommodate Raspberry Pi boards.

Wall mount bracket mounting points

For attaching the bracket to the back of the enclosure

Secured by a single screw

Allowing for quick and easy assembly

Security screw hole in the bracket

For increased protection against theft

Achieve a 45° mounting angle on any surface

Due to engineered design features

Mount to room corners with ease

With the innovative 45° angled bracket

Simple slide and lock mechanism


With built in cable entry point

Recessed lid

Perfect for adding digital printing, labels or keypads

PCB positions

DIMENSIONS FOR EACH POSITION				
PCB MOUNTING POSITION		TING	MAX PCB DIMENSIONS	MOUNTING HOLE SPACING
BASE	A	Upper	93mm x 93mm	85mm x 85mm
	В	Lower	93mm x 65.8mm	58mm x 49mm
LID	с	Upper	91.5mm x 91.5mm	75mm x 75mm
	D	Lower	70mm x 70mm	50mm x 50mm





PART NUMBERS (ENCLOSURE ONLY)				
BODY TYPE	GREY (GY)	BLACK (BK)	WHITE (WH)	
SOLID	CB1500-10SGY	CB1500-10SBK	CBS1500-10SWH	
VENTED	CB1500-10VGY	CB1500-10VBK	CB\$1500-10VWH	

PART NUMBERS (KITS)				
BODY TYPE	GREY (GY)	BLACK (BK)	WHITE (WH)	
SOLID	CB1500-10SGY-KIT	CB1500-10SBK-KIT	CBS1500-10SWH-KIT	
VENTED	CB1500-10VGY-KIT	CB1500-10VBK-KIT	CBS1500-10VWH-KIT	



INCLUDED WITH ENCLOSURE ONLY			
PART DESCRIPTION	QUANTITY PER KIT		
ENCLOSURE (BASE & LID)	1		
LID SCREW (M3 x 10 CSK POZI)	Í		

INCLUDED WITH KIT			
QUANTITY PER KIT			
1			
1			
1			
2			
2			
2			
2			
1			



342

1500 Series **Universal Smart Enclosure**







INDIVIDUAL SIZE DIMENSIONS				
EXTERNAL DIMENSIONS (LxWxH)	INTERNAL DIMENSIONS (LxWxH)	WALL THICKNESS		
100mm x 100mm x 53.2mm	96mm x 96mm x 48.2mm	2mm		

RANGE SPECIFICATION					
STANDARD UNIT INCLUDES	1 x base, 1 x lid, 1 x lid screw (M3 x 10 CSK Pozi)				
	Enclosure		UL94-V0 ABS		
	Wall Mount Bracket		UL94-V0 ABS		
MATERIALS	Wall Mount Lugs		UL94-V0 ABS		
	M3 Insert (Lid)		Brass		
	All Screws / Nuts		BZP (Bright Zinc plated Steel)		
	Grey		RAL7047		
COLOURS	Black		RAL9005		
	White		RAL9003		
COMPLIANCE	RoHS compliant				
IP RATING	Vented		IP30		
IP RATING	Solid		IP40		
OPERATING TEMPERATURE	-10°C to +80°C				
	Standard	Test	Result	Test report	
	UL94	Flammability	VO	TR101	
TEST RESULTS	EN 62208	Thermal stability	Pass	TR105	
	EN 62208	Static loads	200g	TR100	
	EN 62208	Marking	Pass	N/A	
SCREW TORQUE	Self tapping (security and mounting lugs)		0.2Nm	Max insertions =2	
SCREW TORQUE	M3 (Lid and Mounting Lugs)		0.5Nm	Max insertions >1000	
	Country of origin		Great Britain (GB)		
DUDGUACING INFORMATION	Commodity code		39231010		
PURCHASING INFORMATION	Weight	Weight		0.087g	
	Enclosure type		Universal		
OPTIONS	For different colours and materials MOQs will apply.				

Potential industries / applications

Safety monitoring, door entry control, security sensors, social distance monitoring, air detection and more.

Accessories



Universal Wall Mount Bracket (CBWM-10xx*) *Add WH, BK or GY



DIN Rail Mount Bracket (CDR-Bracket)

Mounting options include, but are not limited to:

- Corner mounting (ceiling to wall / wall to wall)
- Irregular walls or corners
- 45° angled up / down / left / right
- Mounted flat to a wall or surface
- Desk mounted at 45°



Customisation options

Digital printing, screen printing, machining / drilling and engraving.

