268 HANDHELD CASES

292 UNIVERSAL ENCLOSURES

318

342

**370** 

# 1500 Series Universal Smart Enclosure

#### **Product overview**

The UK manufactured 1500 Series Universal Smart Enclosure has a premium quality and modern aesthetic with many features and benefits and is available in black, white or grey with the choice of a solid or vented body. The innovative and versatile 45° angled enclosure and bracket allows it to be mounted directly onto irregular corners and walls. It has multi-level PCB mounting bosses with one level designed to fit development boards such as the Raspberry Pi.



### Key features



#### **Multiple PCB mounting points**

Designed to accommodate Raspberry Pi boards.

#### Wall mount bracket mounting points

For attaching the bracket to the back of the enclosure

#### Secured by a single screw

Allowing for quick and easy assembly

#### Security screw hole in the bracket

For increased protection against theft

#### Achieve a 45° mounting angle on any surface

Due to engineered design features

#### Mount to room corners with ease

With the innovative 45° angled bracket

#### Simple slide and lock mechanism


With built in cable entry point

#### Recessed lid

Perfect for adding digital printing, labels or keypads

# **PCB** positions

| DIMENSIONS FOR EACH POSITION |   |       |                       |                          |  |
|------------------------------|---|-------|-----------------------|--------------------------|--|
| PCB MOUNTING<br>POSITION     |   | TING  | MAX PCB<br>DIMENSIONS | MOUNTING<br>HOLE SPACING |  |
| BASE                         | A | Upper | 93mm x 93mm           | 85mm x 85mm              |  |
|                              | В | Lower | 93mm x 65.8mm         | 58mm x 49mm              |  |
| LID                          | с | Upper | 91.5mm x 91.5mm       | 75mm x 75mm              |  |
|                              | D | Lower | 70mm x 70mm           | 50mm x 50mm              |  |





#### PART NUMBERS (ENCLOSURE ONLY) GREY (GY) BLACK (BK) WHITE (WH) SOLID CB1500-10SGY CB1500-10SBK CBS1500-10SWH CB1500-10VGY CB1500-10VBK CBS1500-10VWH VENTED

| PART NUMBERS (KITS) |                  |                  |                   |  |  |
|---------------------|------------------|------------------|-------------------|--|--|
| BODY TYPE           | GREY (GY)        | BLACK (BK)       | WHITE (WH)        |  |  |
| SOLID               | CB1500-10SGY-KIT | CB1500-10SBK-KIT | CBS1500-10SWH-KIT |  |  |
| VENTED              | CB1500-10VGY-KIT | CB1500-10VBK-KIT | CBS1500-10VWH-KIT |  |  |



| INCLUDED WITH ENCLOSURE ONLY |                  |  |  |
|------------------------------|------------------|--|--|
| PART DESCRIPTION             | QUANTITY PER KIT |  |  |
| ENCLOSURE (BASE & LID)       | 1                |  |  |
| LID SCREW (M3 x 10 CSK POZI) | Í                |  |  |

| INCLUDED WITH KIT                                 |                  |  |  |
|---|------------------|--|--|
| PART DESCRIPTION                                  | QUANTITY PER KIT |  |  |
| ENCLOSURE (BASE & LID)                            | 1                |  |  |
| LID SCREW (M3 x 10 CSK POZI)                      | 1                |  |  |
| 45° WALL MOUNT BRACKET                            | 1                |  |  |
| WALL MOUNT LUGS                                   | 2                |  |  |
| LUG SCREWS (NO 4 x 3/8" PAN POZI<br>SELF TAPPING) | 2                |  |  |
| LUG SCREWS (M3 x 10 CSK POZI)                     | 2                |  |  |
| LUG NUTS (M3 FULL NUT)                            | 2                |  |  |
| WALL MOUNT SECURITY SCREW (2.9 x I SELF TAPPING)  | 1                |  |  |



370 CUSTOM SIZED ENCLOSURES

# 1500 Series **Universal Smart Enclosure**





| INDIVIDUAL SIZE DIMENSIONS  |                             |                |  |  |  |
|-----------------------------|-----------------------------|----------------|--|--|--|
| EXTERNAL DIMENSIONS (LxWxH) | INTERNAL DIMENSIONS (LxWxH) | WALL THICKNESS |  |  |  |
| 100mm x 100mm x 53.2mm      | 96mm x 96mm x 48.2mm        | 2mm            |  |  |  |

| RANGE SPECIFICATION    |  |                   |                                |                      |  |
|------------------------|--|-------------------|--------------------------------|----------------------|--|
| STANDARD UNIT INCLUDES | 1 x base, 1 x lid, 1 x lid screw (M3 x 10 CSK Pozi)    |                   |                                |                      |  |
|                        | Enclosure  |                   | UL94-V0 ABS                    |                      |  |
|                        | Wall Mount Bracket                                     |                   | UL94-V0 ABS                    |                      |  |
| MATERIALS              | Wall Mount Lugs  |                   | UL94-V0 ABS                    |                      |  |
|                        | M3 Insert (Lid)  |                   | Brass                          |                      |  |
|                        | All Screws / Nuts                                      |                   | BZP (Bright Zinc plated Steel) |                      |  |
|                        | Grey   |                   | RAL7047                        |                      |  |
| COLOURS                | Black  |                   | RAL9005                        |                      |  |
|                        | White  |                   | RAL9003                        |                      |  |
| COMPLIANCE             | RoHS compliant   |                   |                                |                      |  |
| IP RATING              | Vented   |                   | IP30                           |                      |  |
| IP RATING              | Solid  |                   | IP40                           |                      |  |
| OPERATING TEMPERATURE  | -10°C to +80°C   |                   |                                |                      |  |
|                        | Standard   | Test              | Result                         | Test report          |  |
|                        | UL94   | Flammability      | VO                             | TR101                |  |
| TEST RESULTS           | EN 62208   | Thermal stability | Pass                           | TR105                |  |
|                        | EN 62208   | Static loads      | 200g                           | TR100                |  |
|                        | EN 62208   | Marking           | Pass                           | N/A                  |  |
| SCREW TORQUE           | Self tapping<br>(security and mounting lugs)           |                   | 0.2Nm                          | Max insertions<br>=2 |  |
| SCREW TORGUE           | M3 (Lid and M  | ounting Lugs)     | 0.5Nm                          | Max insertions >1000 |  |
|                        | Country of origin                                      |                   | Great Britain (GB)             |                      |  |
| BURGUAGING INFORMATION | Commodity code   |                   | 3923101000                     |                      |  |
| PURCHASING INFORMATION | Weight   |                   | 87g                            |                      |  |
|                        | Enclosure type   |                   | Universal                      |                      |  |
| OPTIONS                | For alternative colours and materials MOQs will apply. |                   |                                |                      |  |

## Potential industries / applications

Safety monitoring, door entry control, security sensors, social distance monitoring, air detection and more.

#### Accessories



Universal Wall Mount Bracket (CBWM-10xx\*) \*Add WH, BK or GY



DIN Rail Mount Bracket (CDR-Bracket)

# Mounting options include, but are not

- Corner mounting (ceiling to wall / wall to wall)
- Irregular walls or corners
- 45° angled up / down / left / right
- Mounted flat to a wall or surface
- Desk mounted at 45°

limited to:



## **Customisation options**

Digital printing, screen printing, machining / drilling and engraving.

