


50mm wide IP65 limit switches

Product overview


- 50mm width
- Double insulated plastic
- Rated to IP65
- Snap action contacts
-  approved




SPECIFICATION	
Rating	500V
Shock withstand	50g
Impulse withstand voltage	6kV
Working temperature	-25°C to +70°C
Switching frequency	3600 cycles/h
Load factor	0.5
Short circuit protection	10A gG fuse

IP65 PLASTIC CASING	PLUNGER TYPE	MAX ACTUATION SPEED	ACTUATION / NC OPERATION
CE20.00.AP	Steel plunger	0.5ms ⁻¹	15N/30N
CE20.00.BP	Steel roller plunger	0.3ms ⁻¹	12N/30N
CE20.00.FP	Adjustable nylon roller lever	1.5ms ⁻¹	0.10Nm/0.32Nm
CE20.00.HLTP	Nylon actuator with stainless steel spring	1.5ms ⁻¹	0.10Nm/-
CE20.00.TP	Pull action with ring	0.5ms ⁻¹	0.30Nm/-
CE20.00.EP	Nylon roller lever	1.5ms ⁻¹	0.10Nm/0.32Nm
CE20.00.HP	Adjustable stainless steel rod lever	1.5ms ⁻¹	0.15Nm/-/0.30Nm
CE20.00.IP	Nylon roller lever	1.5ms ⁻¹	0.10Nm/0.32Nm
CE20.00.FRP/50	Adjustable lever with adjustable rubber roller	1.5ms ⁻¹	0.10Nm/0.32Nm
CE20.00.CP	Plastic roller	1.0ms ⁻¹	7N/24N
CE20.00.DP	Plastic roller on metal plunger	1.0ms ⁻¹	7N/24N
CE20.00.EP/50	Rubber roller lever	1.5ms ⁻¹	0.10Nm/0.32Nm


Steel plunger




Steel roller plunger




Adjustable nylon roller lever




Nylon actuator with stainless steel spring




Pull action with ring




Nylon roller lever




Adjustable stainless steel rod lever




Nylon roller lever




Adjustable lever with adjustable rubber roller



Plastic roller



Plastic roller on metal plunger



Rubber roller lever

