


60mm wide limit switches

Product overview

- 60mm width
- Metal casing
- Rated to IP66
- Snap action contacts
-  approved



SPECIFICATION	
Rating	500V
Shock withstand	50g
Impulse withstand voltage	6kV
Working temperature	-25°C to +70°C
Switching frequency	3600 cycles/h
Load factor	0.5
Short circuit protection	10A gG fuse

IP66 METAL CASING	PLUNGER TYPE	MAX ACTUATION SPEED	ACTUATION / NC OPERATION
CE31.00.AM	Plain plunger	0.5ms ⁻¹	30N/45N
CE31.00.BM	Steel roller plunger	0.5ms ⁻¹	22N/40N
CE31.00.CM	Side roller lever	1.5ms ⁻¹	12N/30N
CE31.00.HM	Adjustable rod lever	1.5ms ⁻¹	0.15Nm/0.30Nm
CE31.00.GM	Adjustable rod lever	1.5ms ⁻¹	0.15Nm/0.30Nm
CE31.00.EM	Nylon roller lever	1.5ms ⁻¹	0.15Nm/0.30Nm
CE31.00.EM/50	Rubber roller lever	1.5ms ⁻¹	0.15Nm/0.30Nm
CE31.00.FM	Adjustable roller lever	1.5ms ⁻¹	0.15Nm/0.30Nm
CE31.00.FM/50	Adjustable roller lever	1.5ms ⁻¹	0.15Nm/0.32Nm
CE31.00.LBM/90	Stainless steel lateral plunger with vertical roller	1.5ms ⁻¹	30N/50N
CE31.00.LAM	Stainless steel lateral plain plunger	0.5ms ⁻¹	30N/50N
CE31.00.LM	Stainless steel spring multidirectional actuator	1.0ms ⁻¹	0.18N/-

