HANDHELD CASES


292

71 series flanged IP66 enclosures

Product overview

Large robust enclosures with IP66 gasket. Designed for outdoor applications in UV stable, polycarbonate UL94-V0.

- · Mounting flanges on the base
- Recessed cover
- · PCB mounting bosses in the base and cover
- Fitted silicone rubber gasket for dust and moisture resistance
- · Black UV stablised polycarbonate
- · Secured from rear face for security/anti-tamper
- · 71 series has been designed to meet the requirements of NEMA 4X/IP66 ratings





SPECIFICATION	
Materials	Polycarbonate UL94-V0
Operating temperature	-40°C to +120°C
Protection class	71 series has been designed to meet the requirements of NEMA 4X/IP66 ratings
Standard colours	Black
Standard unit includes	Base Cover Silicone gasket 4x stainless steel enclosure screws

PART. NO	LENGTH	WIDTH	HEIGHT
CHD7101BK	139.70mm	88.9mm	38.1mm
CHD7102BK	168.40mm	118.9mm	60.2mm

72 series flanged IP66 enclosures

SPECIFICATION Materials

Operating temperature


Protection class

Standard colours

Product overview

Polished finish polycarbonate enclosures, IP66 rated, for outdoor (waterproof) applications.

- Durable, impact-resistant UV stabilised polycarbonate UL94-VO
- Mounting flanges on the base
- · Recessed cover
- Solid cover or transparent cover option
- PCB mounting bosses in the base and cover
- · Fitted silicone rubber gasket for dust and moisture resistance
- · Captive, stainless steel screws thread into brass inserts
- 72 series has been designed to meet the requirements of NEMA 4X/IP66 ratings





- 40°C to +120°C

Base Cover (inc gasket) Enclosure screws



GREY LID	CLEAR LID	LENGTH	WIDTH	HEIGHT		
CHD7201GY	CHD7211GY	193.8mm	117.6mm	78.5mm		
CHD7202GY	CHD7212GY	222.3mm	133.4mm	83.8mm		

KEY FEATURES

Surface mounting flanges | UL94-VO | PCB stand offs





PLASTIC ENCLOSURES