Shell style/model

Codes

Free cable mount socket connector, female contact

100 CIRCULAR CONNECTORS

# Push-pull connectors female cable mount CCT series


# CCT1S1/05 5 pole

- Premium range of circular connectors
- IP68 sealed using vacuum technology (when connected and using environmental cable clamp)
- Tough, high performance interconnection
- Ideal for harsh and extreme environments
- · Suitable for broadcasting, autosport, military, rail, security and industrial applications
- Key coded to prevent misconnection
- · Will not disconnect when the cable is under load or stress
- · Cable mounting
- Tested to IEC 60512-3-5a
- · Cable clamp required for use with this series





SOCKETS

PART NO.	DESCRIPTION	POLES	SERIES
CCT1S1/05	Female cable	5	CCT series



Contact type	Solder type
Contact diameter	0.7mm
Max. stranded conductor	AWG 21-22
Max diameter	0.79mm
Vtest (contact-shell)	800V(AC) 1300V(DC)
Vtest (contact-contact)	1000V(AC) 1800V(DC)
Rated current	5.2A
Rated voltage	≤160V
Mechanical operation	5000 mating cycles
Housing material	Brass (natural chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Insulator	PPS
Contacts	Brass (gold plated)
Humidity (max)	<=95% [at 60°C /140°F]
Vibration	15g [10 Hz - 2000 Hz]
Shock resistance	100g [6 ms]
Salt spray corrosion	>72 hr
Climatical category	50/175/21
Shielding (min)	75 dB (10 MHz)
Shielding (min)	40 dB (1 GHz)
IP rating	IP68 (when connected and using environmental cable clamp)





## **KEY FEATURES**

Key coded | Cable mounting socket | Cable clamps required

This product should be used with the following cable clamps:

PART NO.	WIRE RANGE
CCV1C/CC	2.6 - 3.1mm
CCV1C/CD	3.1-3.6mm
CCV1C/CE	3.6-4.1mm
CCV1C/CF	4.1-4.3mm



Non IP68 cable clamps also available

Metal	and	rubber	caps	for	SOC

**ACCESSORIES** 

ockets

PART NO.	DESCRIPTION	
ССТ11	Camcirc metal cap for sockets A1	

Ole	

PART NO.	DESCRIPTION
CCT12	Camcirc rubber cap for sockets A1



### ASSOCIATED PRODUCTS

CCA1P1/A05

- CCA Series A1 size plug

page 104

