




# 50mm wide IP66 limit switches

## Product overview


- 50mm width
- Metal casing
- Rated to IP66
- Snap action contacts
-    approved




SPECIFICATION	
Rating	500V
Shock withstand	50g
Impulse withstand voltage	6kV
Working temperature	-25°C to +70°C
Switching frequency	3600 cycles/h
Load factor	0.5
Short circuit protection	10A gG fuse

IP66 METAL CASING	PLUNGER TYPE	MAX ACTUATION SPEED	ACTUATION / NC OPERATION
CE21.00.AM	Plain plunger	0.5ms <sup>-1</sup>	15N/30N
CE21.00.BM	Steel roller plunger	0.3ms <sup>-1</sup>	12N/30N
CE21.00.HM	Adjustable rod lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.GM	Adjustable rod lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.EM	Nylon roller lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.EM/50	Rubber roller lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.FM	Adjustable roller lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.FM/50	Adjustable rubber roller lever	1.5ms <sup>-1</sup>	0.10Nm/0.32Nm
CE21.00.HLTM	Nylon actuator with stainless steel spring	1.5ms <sup>-1</sup>	0.10Nm/-
CE21.00.FRM/50	Adjustable lever with adjustable rubber roller	1.0ms <sup>-1</sup>	0.10Nm/-
CE21.00.IM	Nylon roller lever	1.0ms <sup>-1</sup>	0.10Nm/0.32Nm


Plain plunger




Steel roller plunger




Adjustable rod lever




Adjustable rod lever




Nylon roller lever




Rubber roller lever




Adjustable roller lever




Adjustable rubber roller lever



Nylon actuator with stainless steel spring



Adjustable lever with adjustable rubber roller



Nylon roller lever

